



Gulf Gear MP

Heavy Duty Axle Oil

Product Description

Gulf Gear MP is a high performance gear lubricant designed to provide excellent lubrication in a wide range of automotive transmissions, axles and final drives. It is formulated from high quality base stocks and balanced extreme pressure additives to protect gear components in applications where extreme pressures and shock loading are encountered. It offers effective protection against oxidation degradation and rust & corrosion. It meets the requirements of API GL-5.

Features & Benefits

- Excellent Extreme Pressure properties shields against wear under different operating conditions leading to enhanced equipment durability and lower maintenance costs
- High oxidation stability minimises sludge and deposit formation facilitating longer component life
- Effective rust and corrosion protection reduces wear and extends component life
- Good low temperature fluidity (SAE 80W-90, 85W-90 and 85W-140) reduces wear and enables easy start-up under low ambient temperatures
- Good anti-foam properties ensure film strength for effective lubrication
- Excellent seal compatibility helps minimise leakages and reduce chances of contamination

Applications

- Heavy duty non-synchronized manual transmissions, axles and final drives where API GL-5 quality oils are specified
- On-road passenger cars, light and heavy duty trucks, buses and vans
- Off-highway equipment in construction, mining and agriculture
- Other heavy-duty applications involving hypoid and other gears operating under severe conditions like high speed/shock load, high speed/low torque and/or low speed/high torque
- Not suitable for automatic transmissions

Specifications, Approvals & Typical Properties

Meets the following Specifications		80	90	140	250	80W-90	85W-90	85W-140
API GL-5		X	X	X	X	X	X	X
US MIL-L-2105D		X	X	X	X	X		X
Typical Properties								
Test Parameters	ASTM Method	Typical Values						
Viscosity at 100 °C, cSt	D 445	9.00	16.00	28.00	44.00	16.00	14.5	28.00
Viscosity Index	D 2270	99	97	95	84	101	99	97
Flash Point, °C	D 92	200	210	230	240	210	226	230
Pour Point, °C	D 97	-24	-15	-12	-3	-27	-18	-18
Density @ 15°C, Kg/l	D 1298	0.888	0.895	0.902	0.908	0.894	0.899	0.901

March 2013

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com