

WOLF ESSENTIAL CI-4/SL 15W40

31/05/2018
75702

This engine oil meets the prime requirements of ACEA and API for heavy-duty engines. It combines wear reducing- and cleaning properties into one lubricant.

APPLICATIONS

Suitable for all modern Euro II, III and some Euro IV diesel engines of heavy-duty equipment, making it a great lubricant for mixed fleet maintenance.

FEATURES

Outstanding engine cleanliness and durability

SPECIFICATION LEVEL

ACEA: A3/B4
ACEA: E7 level
API: CG-4
API: CH-4
API: CI-4
MB: 228.3
MB: 229.1

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0,882
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	99,8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13,8
Viscosity index	ASTM D2270		135
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10,5
Pour point	ASTM D6892	°C	-33

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 - 2620 Hemiksem - Belgium
Tel. +32(0)3 870 00 00
www.wolf lubes.com

