

# WOLF ESSENTIAL SL/CF 15W40 B4

31/05/2018  
75611

This engine oil meets the core requirements of ACEA and API for passenger cars. This highly protective formulation quickly neutralises harmful substances entering the engine.

## APPLICATIONS

Suits the needs of older gasoline and diesel passenger car engines, regardless of whether they are equipped with or without turbocharger.

## FEATURES

Engine protection and cleanliness

## SPECIFICATION LEVEL

ACEA: A3/B3  
ACEA: A3/B4  
API: SL/CF

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0,866
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	91,9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13,8
Viscosity index	ASTM D2270		145
Pour point	ASTM D6892	°C	-33

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

**WOLF OIL CORPORATION NV**  
G. Gilliotstraat 52 - 2620 Hemiksem - Belgium  
Tel. +32(0)3 870 00 00  
[www.wolflubes.com](http://www.wolflubes.com)

