

DIESEL TREATMENT

14/11/2017
70311

Cleans the complete fuel system, increases cetane number and restores power and performance. Improves combustion and reduces fuel consumption. Lubricates the diesel pump in case of low sulphur fuel.

APPLICATIONS

For all diesel engines, including common rail, with or without turbochargers. Add the content of one bottle to the fuel tank, prior to filling. The contents of one bottle is sufficient for 50 to 60 litres of diesel fuel.

FEATURES

Cleaning action : superior cleaning of the fuel system.
Combustion improvement.
Fuel consumption reduction.

SPECIFICATION LEVEL

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.860
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	13.4
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	1.2
Flashpoint PMCC	ASTM D93	°C	130

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

