

GASOLINE TREATMENT

22/05/2017
70310

Cleans the complete fuel system including valves, dirty carburettors and clogged injectors. Restores power and performance. Improves combustion and reduces gasoline consumption. Reduces emission of hazardous exhaust gases.

APPLICATIONS

All gasoline (leaded or unleaded) engines, with carburettors or fuel injection. Harmless for catalytic convertors. Add one bottle to the fuel tank before filling with gasoline. One bottle treats 50-60 liters of gasoline. Dosage for normal use : one bottle every 2000km. Dosage for clean-up treatment : one bottle for each tank filling.

FEATURES

Cleaning action : superior cleaning of the fuel system.
Gasoline consumption reduction.
Combustion improvement.

SPECIFICATION LEVEL

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	12.7
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	2.6
Flashpoint PMCC	ASTM D93	°C	128

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfub.com

